

## MORE POSSIBILITIES NEED MORE POWER

### Take it, enjoy it.



# New DT Series: Powerful but still portable Small size with high power to boost various outdoor appliances.

#### **Key Features**

- High Power/Capacity output ratio, 50% more than competitors \*
- PowerRush inverter technology, better for AC resistive loads \*\*
- Super-fast charging, 1-hour recharge to 80%
- Prominent LED light effects, easy to monitor device status
- Builit-in EPS (Emergency Power Supply), no fear of unexpected blackouts
- Parallel to double AC output and battery capacity \*\*\*

<sup>\*</sup> Power/capacity ratio of DT Series is designed to be over 1.5

<sup>\*\*\*</sup> AC resistive devices with wattage ratings between 800W to 1600W for DT800 and 1500W to 3000W for DT1500, such as hair dryer, electric kettle, coffee machine, toaster, space heater, etc.

<sup>\*\*\*</sup> Only available on DT1500.



### **Technical Specifications**





PowerRush





DT800	
Power	800W continuous, 1600W Peak
Capacity	495Wh
Battery Pack	18V/27,5Ah, NCM Cell
Cycle Life	>600 cycles (100% DOD, 80% EOL)
Dimensions	292x231x195mm
Weight	7 kg
Input	1xAC IEC C14 (495W Max.) 1x DC XT60 (200W Max.)
Output	1x AC CEE 7/4 (800W Rated, 1600W Surge) 2x USB-A QC3.0 (18W Max.) 1x USB-C (18W Max.) 1x USB-C (100W Max.) 1x CIG. (13.6V/10A, 136W Max.)
Other Features	PowerRush, Fast Charging, EPS
Certifications	CE, RoHS, UL, FCC, PSE, UN38.3, SDS





Paralle



PowerRush



1-Hour Recharge to 80%



400W Solar Input



Dual PD 100W

DT1500	
Power	1500W continuous, 3000W Peak
Capacity	998Wh
Battery Pack	41,6V/24Ah, LFP Cell
Cycle Life	>2000 cycles (100% DOD, 80% EOL)
Dimensions	430x262x289mm
Weight	17 kg
Input	1xAC IEC C14 (998W Max.) 1x DC XT60 (400W Max.)
Output	2x AC CEE 7/4 (1500W Rated, 3000W Surge) 2x USB-A QC3.0 (18W Max.) 2x USB-C (100W Max.) 1x CIG. (13.6V/10A, 136W Max.)
Other Features	PowerRush, Fast charging, EPS, Parallel
Certifications	CE, RoHS, UL, FCC, PSE,UN38.3, SDS